

INSTRUCTION OF INSTALLATION STRAPS WITH PROTECTIVE PAD

(Applied in cases: Pico, Quart, Elipe, Neva, Matero, Andaz)

Strap with protective pad consists of a belt and a pad.

Elements of the belt:

- carbiner fixed (metal component, which is sewn to the belt)



- carbiner moving (the metal part is not sewn to the belt)



- belt



- plastic regulator (element sewn) used to adjust the length of strap



Protective pad:

- smooth, non-slip surface has the protective function
- the back side there are 3 fixing elements (ie. loops)



Adjusting the length of straps followed by a plastic regulator through its sliding on the belt. Sliding plastic regulator toward the carbiner fixed - shorten its length. Sliding plastic regulator in the direction of the moving carbiner - can extend its length.

There are two ways of mounting these elements so as to provide a practical shoulder straps for carrying on the back.

The first way - if you want to get the maximum length of the strap.

1. By sliding the plastic regulator extend the length of the belt.



2. Carbiner fixed put it through the loops contained on protector (plastic regulator does not pass through any belt loop).



3. Clip the straps in the case - carabiner fixed to the upper brackets designed for straps.



4. Clip straps with carabiner moving to the lower brackets designed for straps.



The second method - if you want to shorten the length of the strap.

1. By sliding the plastic regulator shorten the length of the belt.



2. Carbine moving postpone through the loops contained on protector (plastic regulator does not pass through any belt loop).



3. Clip straps to the case as in the way first - points 3 and 4.



A single belt with pad can be used to carry the case on his shoulder. To do this, connect the belt with the pad in the first way, then attach it to a handle designed to be worn on the shoulder.

If you have any doubt, do not hesitate to contact us. We will gladly answer all your questions.

